



TRENCH TO BE BRACED OR SHEETED AS NECESSARY FOR THE SAFETY OF THE WORKMEN, AND THE PROTECTION OF OTHER UTILITIES.

NOTE: MINIMUM COVER TO BE BELOW OFFICIAL STREET GRADE.

TRACE WIRE CONNECT TO TEST STATION ADJACENT TO F. H.

BEDDING FROM 12" ABOVE THE TOP OF PIPE TO 6" BELOW BOTTOM OF PIPE

| PIPE DIAMETER | MINIMUM WIDTH | MAXIMUM WIDTH |
|---------------|---------------|---------------|
| 4" | 1'-8" | 2'-4" |
| 6" | 1'-10" | 2'-6" |
| 8" | 2'-0" | 2'-8" |
| 12" | 2'-4" | 3'-0" |

SQUEEGE OR APPROVED EQUAL

STABILIZATION MATERIAL, GRADUATION 3/4" TO 1 1/2" WASHED ROCK, TO DEPTH AS REQUIRED TO OBTAIN A STABLE SUBGRADE

TYPICAL TRENCH SECTION

SCALE: N. T. S.



CITY OF FEDERAL HEIGHTS
 COLORADO
 STANDARDS DRAWINGS
 MARCH 2010

TYPICAL TRENCH SECTION
 FOR WATER LINE

DRAWING #
3-1